



PRODUCT DATA SHEET

EX25 Pro-White™ RIGID WHITE ADHESIVE TAPE

DESCRIPTION

- ✦ Bleached White woven fabric based rigid adhesive tape
- ✦ Proprietary White Synthetic Rubber Adhesive Formulation
- ✦ Made in USA by Jaybird & Mais, Inc.
- ✦ Computerized Unwind Tension
- ✦ Serrated Edge Cut (SEC)
- ✦ Non-sterile, for external usage and disposable
- ✦ Hand Tearable (bi-directional)
- ✦ Stable Adhesive Coating when exposed to heat
- ✦ Store Cool & Dry for maximum performance
- ✦ 100% Latex Free
- ✦ Not made with Natural Rubber Latex

PHYSICAL PROPERTIES*

TEST/REFERENCE	AVERAGE VALUE
Tensile Strength (PSTC-31)	43 lbs./linear inch @ 1½ width
Adhesion 180° Peel to SS (PSTC-101)	35-ounces/linear inch
Adhesion 180° Peel to Backer (PSTC-101)	29-ounces/linear inch
Thickness	10-11 mils

* Pressure Sensitive Tape Council methods used when applicable. Testing represents typical performance values (averages)

STANDARD SIZE & PACKAGING

PRODUCT NO	SIZE	SIZE (METRIC)	ROLLS/CASE	STOCK ITEM
EX25-1015S	1" x 15 yards	2,5cm x 13,7m	48	YES
EX25-1515S	1½" x 15 yards	3,8cm x 13,7m	32	YES
EX25-2015S	2" x 15 yards	5,0cm x 13,7m	24	YES
EX25-3810S	1½" x 10.9 yards	3,8cm x 10m	32	NON-STOCK
EX25-1010S	1" x 10 yards	2,5cm x 9,1m	200	YES
EX25-2010S	2" x 10 yards	5,0cm x 9,1m	100	YES
EX25-0510S	½" x 10 yards	1,3cm x 9,1m	400	YES
EX25-0505S	½" x 5 yards	1,3cm x 4,6m	672	YES
EX25-05025S	½" x 2½ yards	1,3cm x 2,3m	1008	NON-STOCK

RECOMMENDED STORAGE

The above product should be stored in a cool dry environment for best results of product performance. Average recommended temperature for storage: 60° to 72° Fahrenheit (19.4° to 22.8° Centigrade)

Technical information provided by Jaybird & Mais, Inc. is based on experience and/or tests believed to be reliable, but their accuracy is not guaranteed and the results may not be relevant to every user's application. For this reason, Jaybird & Mais, Inc. does not accept responsibility or liability, direct or consequential, arising from reliance upon any information provided and the user should determine the suitability of the products for their intended use.

